


IN THE CLAIMS:

Claims 1-5 (Canceled)

6. (Currently Amended) The terminal equipment for cable television according to claim 3 15, wherein said controller switches a selector subsection of said second tuner section in response to a manipulation signal input thereto, to supply the image signal from said second tuner section to said radio-transmitter section or a terminal connected to a picture-recording device.

Claims 7-13 (Canceled)

 14. (Currently Amended) The terminal equipment for cable television according to claim 4 15, wherein said slave terminal further includes a remote controller receiving section for receiving a remote control signal supplied from a wireless remote controller.

15. (New) Terminal equipment connected to a cable television station of cable television to receive a cablecast signal for television programming delivered from the cable television station, comprising:

a master terminal including a first tuner section for receiving a cablecast signal for television programming delivered from the cable television station and applying an image signal produced from the cablecast signal to a first television receiver, at least one second tuner section for receiving a cablecast signal for television programming

delivered from the cable television station and outputting an image signal produced from the cablecast signal, and a radio-transmitter section connected to said second tuner section to radio-transmit the image signal output from the second tuner section, wherein said second tuner section has a selector subsection for switching between a terminal connected to a picture-recording device and said radio-transmitter section to apply the image signal to the terminal or said radio-transmitter section;

Handwritten initials: H, Q, and a signature
at least one slave terminal including a radio-receiving section for receiving the image signal transmitted from said radio-transmitter section of said master terminal, and applying the image signal received by said radio-receiving section to a second television receiver; and

a message signal outputting section for outputting a message signal for displaying a selecting state of said selector subsection on the second television receiver, to transmit the message signal through said radio-transmitter section to said slave terminal, when the selector subsection is switched to send the image signal from said second tuner section to the picture-recording device.
